

CleverCam

Discover 4k Ultra-High Definition

CleverCam is a 4K ultra-high definition ePTZ camera with a sleek, eye-catching design. CleverCam employs advanced ISP processing algorithms to provide vivid, vibrant images with uniform clarity, brightness, strong colour layering, high resolutions and fantastic colour rendition. With it's great functionality and superior performance, CleverCam is easy and convenient to install and maintain.



MIC

Built-in two omni-directional
MIC pickups

Sensor

1/2.8 inch high quality
CMOS sensor

Audio/Visual

Multiple Audio/Visual
Compression Standard



Key Features



Ultra HD 4K resolution



10x digital zoom



Easy to install and use
on any device



Wide field of view with
83° wide angle and small
distortion lens options



Auto framing using face-
detection algorithm



1/2.8 inch high quality
CMOS sensor



Video output interface
USB 3.0 Plug and play



Built-in 2 omni-directional
MICs. With unique noise
suppression algorithm

Auto Framing

Employs a superior face detection algorithm to intelligently and automatically frame an image according to the number of people in the scene, as well as, focusing more on those that are in the middle.

Easy Installation

CleverCam is equipped with a mould clamp for easy installation on any device, such as, an LCD screen, laptop, table and tripod. No need to download any drivers; just plug and play using the USB 3.0 connection.

Technical Specification

View Angle	95°(D) / 83°(H) / 46°(V)
Focal Length	f=3.24mm
Iris	F2.1
Image Sensor	1/2.8 Inch High Quality 4K CMOS Sensor
Effective Pixels	8.28MP, 16:9
Video Output	USB3.0(Type B), audio video outputs LAN: 10M/100M/1000M adaptive Ethernet port,audio output supported (The default model without LAN)
Video Compression	USB 3.0:YUV2, NV12, MJPG, H.264, H.265 LAN:H.264, H.265
Audio Input	2 Micro omnidirectional pickups
Video Resolution	Main Stream: 3840×2160 @30fps, 1920×1080P @30fps / 25fps, 1280×720P @30fps / 25fps Sub Stream:1280×720P @30fps / 25fps, 640×480P @30fps / 25fps 320×172P@30fps / 25fps
Digital Zoom	10X
Illumination	0.1Lux (F1.8, AGC ON)
DNR	2D&3D DNR
Super Low Illumination	On/Off
Focus	Auto / Manual / One Push
White Balance	Auto / Manual / One Push//3000K/3500K/4000K/4500K/5000K/5500K/6000K/6500K/7000K
Exposure	Auto / Manual
Backlight Contrast	On/Off
SNR	>55db

USB

Video Compression	YUY2, NV12, MJPG, H.264, H.265
Operation Systems	Windows 7 (1080P or lower), Windows 8.1, Windows 10; macOS™, 10.10 or higher, Linux (UVC support); Android
USB Audio	Support
USB Protocol	UVC, UAC
USB Control	EPTZ
Hardware Requests	2.4 GHz Intel@ Core 2 Duo Processor or better, 2GB Capacity or more, USB 2.0 Input (USB3.0 for 4K)

Other Parameters

Working Voltage and Current	USB power supply	5v
	POE power supply	48V
	USB power supply	1A (max)
	POE power supply	0.104A (max)
Power Consumption	5W (max)	
Stored Temperature	-10°C ~ +60°C	
Stored Humidity	20% ~ 95%	
Working Temperature	-10°C ~ +50°C	
Working Humidity	20% ~ 80%	
Dimension (W*H*D)	180mm × 42.5mm × 46.3mm	
Weight Accessory	Around 0.3kg	
	User Manual, USB3.0 cable, Remote Control	

© 2021 Clevertouch. All rights reserved. Sahara Presentations Systems PLC. is part of the Boxlight group of companies, and the owner of trademarks in several global jurisdictions including but not limited to Clevertouch, the Clevertouch logo, UX Pro, IMPACT™, IMPACT Plus™, Impact MAX, CleverLive, LUX, Lynx, CleverMessage, Cleverstore and Clevershare. All third-party trademarks (including logos and icons) referenced by Clevertouch remain the property of their respective owners. Unless specifically identified as such, Clevertouch's use of third-party trademarks does not indicate any relationship, sponsorship, or endorsement between Clevertouch and the owners of these trademarks. Applicable Terms and Conditions for warranty and support available at clevertouch.com/about/warranty. All weights and dimensions are approximate. Product specifications are subject to change without notice. Clevertouch.com.