

MultiSync® ME651  
LCD 65" Message Essential Large Format Display

## Datasheet



### Your pathway to signage digitisation

Offering a professional feature set and NEC's renowned high reliability, yet at a very attractive price point, the NEC ME series presents the perfect opportunity to digitise your signage. Only commercial-grade displays are capable of delivering reliable, long-life performance and the ME Series presents lower budget business operators the upgrade path to professional digital signage without requiring specialist expertise.

Primed with an integrated USB MediaPlayer, the ME series offers out-of-the-box playback which can be easily upgraded thanks to NEC's modular approach. Enjoy all the flexibility you need to create, schedule and broadcast expert signage content, meaning your messaging is always fresh and up to date. Capable of landscape or portrait orientation and up to 18/7 hours continuous operation, local retailers, restaurants and small business enterprises can deliver dynamic advertising and infotainment to their customers whilst benefiting from the efficiencies gleaned through digitisation.

### Benefits

**Modern and slim design** – robust yet elegant allowing for an unobtrusive integration into any application and environment.

**Secure remote management** – control your devices remotely and securely using NEC NaviSet Administrator 2; proactively manage maintenance requirements saving time and resources

**Ease of use and operation** – smart installation, operation and maintenance functionality ensures accurate performance over the entire lifetime of the display saving time, effort and resources.

**Future Ready Connectivity** – featuring multiple industry standard digital and analogue signal inputs for flexible integration into AV infrastructures.

**Effortless content playback** – the integrated USB media player supports various image video file formats for effortless and standalone content playback.

## Product Information

Product Name	MultiSync® ME651
Product Group	LCD 65" Message Essential Large Format Display
Order Code	60005062

## Display

Panel Technology	IPS with Direct LED backlights
Screen Size [inch/cm]	65 / 163.9
Aspect Ratio	16:9
Brightness [cd/m <sup>2</sup> ]	400
Contrast Ratio	≥ 8000:1 <sup>1</sup>
Viewing Angle [°]	178 horizontal / 178 vertical (typ. at contrast ratio 10:1)
Response Time (typ.) [ms]	6
Panel Refresh Rate [Hz]	60
Haze Level [%]	Standard (1)
Supported Orientation	Landscape; Portrait

## Synchronisation Rate

Horizontal Frequency [kHz]	26 - 135
Vertical Frequency [Hz]	23 - 86

## Resolution

Native Resolution	3840 x 2160			
Supported Resolutions	4096 x 2160; 3840 x 2160; 1920 x 2160; 1920 x 1200;	1920 x 1080; 1650 x 1050; 1600 x 1200; 1440 x 900;	1400 x 1050; 1366 x 768; 1360 x 768; 1280 x 1024;	1280 x 720; 1024 x 768

## Connectivity

Input Video Digital	1 x DisplayPort (with HDCP); 2 x HDMI (with HDCP)
Input Audio Digital	1 x DisplayPort; 2 x HDMI
Input Control	LAN 100Mbit; remote control wire (3,5mm jack); RS232
Output Audio Analogue	1 x 3,5 mm jack
Input Detect	Custom; First; Last

## Open Modular Intelligence

Intel® SDM	accepts Intel® Smart Display Modules Large and Small up to 66 W
Compute Module Slot	RPi Compute Module 4

## Sensors

Temperature Sensor	Integrated, 3 sensors, triggered actions programmable
--------------------	---

## Electrical

Power Consumption Eco/max. [W]	165 shipping
Power Savings Mode [W]	< 0.5; < 2 (Networked Standby)
Power Management	VESA DPMS
Power Supply	100-240 V AC; 50/60 Hz; internal

## Environmental Conditions

Operating Temperature [°C]	+0 to +40
Operating Humidity [%]	20 to 80
Storage Humidity [%]	10 to 90
Storage Temperature [°C]	-20 to 60

## Mechanical

Dimensions (W x H x D) [mm]	1,462.3 x 837.3 x 68.1
Weight [kg]	29.4
Bezel Width [mm]	14.9
VESA Mounting [mm]	4 holes; 400 x 400 (FDMI); M8
Ingress Protection	IP5x (front); IP2x (back)
Packaging Dimensions (W x H x D) [mm]	Box 1: 1,736 x 1,033 x 280
Packaging Weight [kg]	Box 1: 41.7
Colour Bezel	Pantone 426M (black)
Material	Metal

## Available Options

Accessories	Feet (ST-65M); Soundbar; Trolley (PD02MHA, PD03MHA, PDMHM-L); Wall mount (PDW T XL-2)
-------------	---

## Green Features

Energy Efficiency	Energy consumption: 156 kWh/1000 h; Energy efficiency class: G; LED backlight
Ecological Standards	EnergyStar 8.0

## Additional Features

Special Characteristics	DICOM Simulation
Safety and Ergonomics	Energy Star 8.0
Pixel Failure Class	ISO 9241-307, Class 1
Audio	Integrated Speakers (10 W + 10 W)
Shipping Content	2x AAA batteries; Display; HDMI Cable; Power Cable; Remote Control; Setup Manual; User Manual
Warranty	3 years warranty incl. backlight; additional services available
Operating Hours	18/7
External Control	AMX NetLinx Support; ASCII Control Commands; HDMI CEC; HTTP Browser; PjLink; Scheduled Timer; Scheduled Timer; SNMP
Remote Management	Automated Email Alerts; NEC NaViSet Administrator 2
Security	Disable HW Buttons; Disable IR Functionality; Emergency Notification

<sup>1</sup> out of the box conditions, local dimming ON

This document is © 2021 Sharp NEC Display Solutions Europe GmbH.

All rights reserved in favour of their respective owners. All hardware and software names are brand names and/or registered trademarks of the respective manufacturers. All specifications are subject to change without notice. Errors and omissions are accepted. 10.03.2021