



DU857 is a Compact, Portable, High Brightness Projector with Stunning Colors and Diverse Connectivity

FEATURES

- DLP® technology with BrilliantColor™ for vibrant and rich picture quality
- 5,000 lumens high brightness with 4,000 hours lamp-life in Eco Mode
- Easy image corrections with 4 corner geometric adjustment, horizontal and vertical keystone corrections
- 1.5x zoom ratio for installation flexibility
- Power over USB-A (5V/1.5A) enables connection of HDMI based multimedia or NovoConnect wireless collaboration devices: NC-X300, NovoPro
- New On-screen display (OSD) control menu for ease of use and improved control over viewing options
- viviBlack enhances black level for higher contrast ratio
- Supports network control
- Environmentally friendly design and compliance



DU857 projector is suited for installations in meeting rooms for professional usage

The DU857 projector brings outstanding performance with its WUXGA resolution and a high degree of vibrancy thanks to 5,000 lumens of brightness and a contrast ratio of 15,000:1. With a weight of 3.4 kg and a flexible 1.5x zoom ratio it allows for easy carrying between different meeting rooms, and is ideal for taking on the road. With advanced color technology, multiple modes and hardware features the projector provides lasting, reliable and precise colors, it is offering the optimum picture performance for any use in many environments.



DU857

SPECIFICATIONS

Image	Display Type	Single chip DLP® Technology by Texas Instruments
	Brightness	5000 ANSI Lumens
	Native Resolution	WUXGA (1920x1200)
	Max. Supported Resolution	WUXGA (1920x1200)@60Hz
	Contrast Ratio	15,000:1
	Native Aspect Ratio	16:10
	Keystone Correction	+/- 30 Degree; +/- 30 Steps
	Optical	Throw Ratio
Image Size (Diagonal)		26.7" - 334"
Projection Distance		1.2 - 10 m
Projection Lens		F=2.42 - 2.97 , f=20.70 - 31.05 mm
Zoom Ratio		1.5x
Offset		114.9% +/- 5%
Focus		Manual
Features		Features
Compatibility	Video	SDTV (480i, 576i) / EDTV (480p, 576p) / HDTV (720p, 1080i, 1080p), NTSC (M, 3.58/4.43 MHz), PAL (B,D,G,H,I,M,N) SECAM (B,D,G,K,K1,L)
Connectivity	I/O Connection Ports	VGA-In (15pin D-Sub), HDMI Number of Ports 1.4a (x2), Audio-In (Mini-Jack), VGA-Out (15pin D-Sub), Audio-Out (Mini-Jack), RJ45, 12v Trigger (Ø3.5mm mini jack), RS-232, USB A (x2 (5V/ 1.5A) (Power Only)), USB miniB (Service)
General	Lamp Life and Type	3,000/4,000/5,000 Hours (Normal/ Eco./Dynamic Eco), 310W/250W
	Speakers	10W (Mono)
	Dimensions (W x D x H)	314 x 213 x 126 mm
	Weight	3.4 kg
	Noise Level	36dB /31dB (Normal/Eco. Mode)
	Power	AC 110-240V, 50/60Hz
	Warranty	Standard Warranty: 3 years projector / 1 year on lamp or 1.000 hours whichever comes first
	Standard Accessories	VGA Cable, Quick Start Guide, Warranty Card (by region), Remote Controller (with battery), AC Power Cord
	Optional Accessories	Spare Lamp P/N (5811120589-S), Remote Control P/N (5042149001)
	UPC Code	813097 024732