



Versatile Portable Projector with High Brightness



FEATURES

- 4000 ANSI lumens of brightness and 30,000:1 contrast ratio for clear, crisp and bright presentations
- WXGA (1200 x 800) native resolution scalable up to a maximum WUXGA (1920 x 1200) resolution
- A long lamp life up to 10,000 hours for low Total Cost of Ownership (TCO)
- 6 segment (RYGCWB) colour wheel for vivid colour reproduction.
- HDMI inputs for high definition content with the same high quality
- 3D Ready for for creating immersive, interactive, and visually stunning experiences across various applications.
- The USB-A power provides for seamless integration with multimedia devices.
- Audio ready with built-in 10 watt audio speaker, audio-in and audio-out ports
- Compact and lightweight at 2.6kg for easy portability

From meeting room to presentations anywhere on the road

The DW350 is a native WXGA digital projector from Vivitek. It features DLP® and BrilliantColor™ technologies to display distinct, vibrant images in a widescreen format. The Vivitek DW350 features numerous connectivity options including two HDMI v1.4 ports, a brightness level of 4000 ANSI Lumens and a 30,000:1 contrast ratio. With its light weight and compact for easy installation that will fit any budget.



DW350 SPECIFICATIONS

Image	Display Type	Single chip DLP® Technology by Texas Instruments
	Brightness	4000 ANSI Lumens
	Native Resolution	WXGA (1280 x 800)
	Max. Supported Resolution	WUXGA (1290 x1200) @60Hz
	Contrast Ratio	30,000:1
	Native Aspect Ratio	16:9
	Keystone Correction	Vertical: +/-30°
Optical	Throw Ratio	1.55~1.73 : 1
	Image Size (Diagonal)	29.7"~301.5"
	Projection Distance	1.1m -10m
	Projection Lens	F=2.47 - 2.66, f=20.4 - 24.48mm
	Zoom Ratio	1.1x
	Offset	116% ±5%
Features	Features	3D Ready(DLP link, PC+Video), Direct 3D (HDMI 1.4a), 3D Mandatory Formats supported (top/bottom, right/left, frame sequential)
Connectivity	I/O Connection Ports	VGA-In (15pin D-Sub) (x1), HDMI Number of Ports 1.4b (x1), Composite Video, Audio-In (Mini-Jack), Audio-Out (Mini-Jack), RS-232, USB A (x1 (power 5V/1.5A)), USB miniB (Service)
General	Lamp Life and Type	5,000 / 7,000 / 10,000 Hours (Normal / Eco. / Long Eco. Mode), 203W
	Speakers	10W
	Dimensions (W x D x H)	313 x 236 x 114mm
	Weight	2.6 kg
	Noise Level	31dB / 27dB (Normal / Eco. Mode)
	Power	Supply: AC 100-240V, 50/60Hz Consumption: 210W (Eco. Mode), 250W (Normal Mode), <0.5W (Standby)
	Warranty	Entry Warranty: 2 years projector / 1 year on lamp or 1.000 hours whichever comes first, Education Warranty: 5 years projector / 3 years on lamp or 2.000 hours whichever comes first
	Standard Accessories	Quick Start Guide, Warranty Card (by region), Remote Controller (with battery), AC Power Cord
	Optional Accessories	Spare Lamp P/N (XX5810005600), Remote Control P/N (SS-45-76U01G023-VV)
	UPC Code	813097023322