

LCD 49" Essential Large Format Display

NEC MultiSync® E498



Functionality you need, at the price you want

A professional solution for low-budget applications, the E series forestalls the lure of domestic TVs which are not fit-for-purpose. Designed for the rigours of commercial usage, the E Series delivers the functionality and reliability you need, at the price you want.

An integrated MediaPlayer supports native UHD resolution and High Dynamic Range (HDR) for deep contrasts and natural looking content playback with auto-play function. Requiring no additional cables, external devices or signage software, the USB MediaPlayer enables a simple seamless professional signage solution. Meanwhile, a 10W USB interface supports connection of external devices should additional computing power be required.

For instant start-up in meeting spaces, inputs are detected automatically with easy switching between HDMI sources. Facilities managers will welcome the ability to remotely control their digital estate via the network thanks to the integrated LAN and NEC's NaviSet Administrator 2 functionality making the E Series the perfect choice for corporate meeting rooms and entry level digital signage.

Benefits

Slim Design and Integrated Speakers – the aesthetic design is pleasing to the eye and enables easy, low cost installation.

Future Ready Connectivity – featuring multiple industry standard digital and analogue signal inputs for flexible integration into AV infrastructures.

Effortless content playback – the integrated USB media player supports various image video file formats for effortless and standalone content playback.

Professional integration – enriched with essential RS232 functionality, IR and button lock out as well as digital audio output S/PDIF, the display can easily be integrated into professional applications in public environments.

Standalone operation – the display is designed for straightforward standalone operation due to integrated USB media player, speakers and scheduling functionality.

Specifications

Product Information

Product Name

NEC MultiSync® E498

Product Group

LCD 49" Essential Large Format Display

Order Code

L50E498

Display

Panel Technology

IPS with Direct LED backlights

Active Screen Area (W x H) [mm]

1,073.8 x 604

Screen Size [inch/cm]

48.5 / 123.2

Aspect Ratio

16:9

Pixel Pitch [mm]

0.280

Brightness [cd/m²]

400

Contrast Ratio (typ.)

1200:1

Viewing Angle [°]

178 horizontal / 178 vertical (typ. at contrast ratio 10:1)

Colour Depth [bn]

1.073 (10bit)

Response Time (typ.) [ms]

8

Panel Refresh Rate [Hz]

60

Haze Level [%]

Standard (1)

Supported Orientation

Landscape; Portrait

Resolution

Native Resolution

3840 x 2160

Supported Resolutions

1280 x 720;	3840 x 2160;	720 x 480;
1920 x 1080;	4096 x 2160;	720 x 576
1920 x 1200;	640 x 480;	

Synchronisation Rate

Horizontal Frequency [kHz]

15 - 136

Vertical Frequency [Hz]

24 - 75

Connectivity

Input Video Analogue

1 x VGA; Component (RCA); Composite (RCA)

Input Video Digital

3 x HDMI

Input Audio Analogue

1 x 3,5 mm jack

Input Audio Digital

3 x HDMI

Input Control

LAN 100Mbit; RS232

Input Data

1 x USB 2.0 (MediaPlayer); 1 x USB Typ-C (5V/3A, power for external devices)

Output Audio Analogue

1 x 3,5 mm jack

Output Audio Digital

1 x SPDIF

Remote Control

Remote Control IR; RS-232C (9-pin D-sub) Input

Sensors

Ambient Light Sensor

Integrated, triggered actions programmable

Temperature Sensor

Integrated, 1 sensors, triggered actions programmable

Electrical

Power Consumption [W]

109 shipping

Power Savings Mode [W]

< 0.5; < 2 (Networked Standby)

Power Supply

100-240 V AC; 50/60 Hz; internal

Environmental Conditions

Operating Temperature [°C]

+0 to +40

Operating Humidity [%]

10 to 80

Storage Humidity [%]

5 to 85

Storage Temperature [°C]

-10 to +60

Mechanical

Dimensions (W x H x D) [mm]

Without stand: 1,102.8 x 634 x 71.6

Weight [kg]

Without stand: 12.4

Bezel Width [mm]

12.5 (left, right and top); 13.9 (bottom)

VESA Mounting [mm]

4 holes; 400 x 200 (FDMI); M6

MediaPlayer

Supported File Storage / File System

USB 2.0 / FAT16, FAT32

Supported Image Formats

JPG (baseline, progressive, RGB, CMYK); max. resolution 15360 x 8640

Supported Video Formats

MPG (MPEG1/2/4, max res 1080p@30Hz); MP4 (MPEG2/4, H.263, H.264, HEVC/H.265, max res 3840x2160@60Hz); TS (MPEG2, H.264, HEVC/H.265, max res 3840x2160@60Hz); audio: LPCM, MP3, AAC; WMV (video H.264, Windows Media Video 9, max res 1080p@30Hz, audio WMA 9, WMA 10 Pro)

Supported Audio Formats

MP3 (MP3); max. bit-rate 320 kBit/s

Available Options

Accessories

Feet (ST-32E2); Trolley (PDMHM-L); Wall mount (PDW S 32-55L)

Regulatory

Safety and Ergonomics

EMC Class B; Energy Star 8; FCC; PSB; RCM; TÜV GS; UL/C-UL; VCCI

Green Features

Energy Efficiency

Energy consumption: 77 kWh/1000 h; Energy efficiency class: G; LED backlight

Ecological Standards

EnergyStar 8.0

3rd Party Certifications

Crestron

Certified for Crestron CCV2 and XiO Cloud

Additional Features

Special Characteristics

Ambient Light Sensor; Audio settings with equalizer; CEC Support; Colour temperature mode; Display Browser Control; Energy saving picture mode; HDMI with UHD at 60 Hz; HDR Gamma Support (HLG, PQ); Mac and Windows compatible; NaViSet Administrator 2 - free download; Powered USB-Port; Retail picture mode; Scheduler; SNMP Support; USB Media Player

Audio

Integrated Speakers (10 W + 10 W)

Shipping Content

2x AAA batteries; Display; HDMI Cable; Power Cable; Remote Control; Setup Manual

Warranty

3 years warranty incl. backlight

Operating Hours

16/7



TÜV GS



VCCI



RCM

This document is © 2026 Sharp Display Solutions Europe GmbH.

All rights reserved in favour of their respective owners. All hardware and software names are brand names and/or registered trademarks of the respective manufacturers. All specifications are subject to change without notice. Errors and omissions are excepted. 27.04.2026